

PANEL



**Model: UFO5W**  
 UFO size: 110mm  
 Case Size: 22\*4.5\*3.5cm  
 Hole cutting size: 100mm  
 Light source: COB 5W  
 Voltage: AC220-240V 50-60Hz  
 Battery: Ni-CD 6V 800mAh  
 Duration: 2hours  
 Material: Iron UFO +Iron case material  
 CCT: 3000k/6500k



**Model: UFO3W**  
 UFO size: 110mm  
 Case Size: 22\*4.5\*3.5cm  
 Hole cutting size: 100mm  
 Light source: LED 3W  
 Input voltage: 220-240V 50-60Hz  
 Battery: Ni-CD 3.6V 1500mAh  
 Duration: 2hours  
 Material: Iron UFO +Iron case material  
 cct: 3000K/6500K



**Model: s908**  
 UFO size: 140mm/110mm  
 Case Size: 130\*45\*25mm  
 Hole cutting size: 75mm  
 Light source: LED 3W COB 6000k  
 Voltage: AC85-265V 50-60Hz  
 Battery: Lithium battery 3.7V 2400mAh  
 Duration: 2hours  
 Material: Plastic UFO +Plastic case material



**Model: S918**  
 UFO size: 50mm  
 Case Size: 180\*25\*33mm\*2pcs  
 Hole cutting size: 40mm  
 Light source: SMD3535 LED 3W  
 Input voltage: 220-240V/50-60Hz  
 Battery: Lithium battery 3.7V 2000mAh  
 Duration: 3hours  
 Material: Plastic UFO +plastic case material  
 cct: 3000K/6500K



**Model: S909**  
 Item size: 130\*45\*25mm  
 Voltage: AC85-265V 50-60Hz  
 Light source: LED 3-50W  
 Battery: Lithium battery 3.7V 2400mAh  
 Charging Time: 24hours  
 Duration: 60-120mins  
 Material: Plastic  
 The emergency driver only support the lamps with external driver  
 (Such as LED panel light, LED downlight)

PANEL



S920-60



S920-100



S920-140

**Model: S920-60**  
 Input voltage: 220V ± 10% 50Hz  
 Input: 3W  
 Material: PC  
 LED SMD 3535 6V 3W  
 Battery: Lithium 3.7V 1800mAh  
 Charge time: 16-24hours  
 Duration time: 1.5hours/3hours  
 non-maintain type  
 IP20  
 Product size L: 415\*33\*31mm  
 Installation: Recessed mounted  
 Cut hole: 40mm  
 Diameter: 60mm  
 Box size: L300\*W70\*H65mm 1pc/box  
 Carton size: 48\*32\*35CM/30PCS/14.5KG

**Model: S920-100**  
 Input voltage: 220V ± 10% 50Hz  
 Input: 3W  
 Material: PC  
 LED SMD 3535 6V 3W  
 Battery: Lithium 3.7V 1800mAh  
 Charge time: 16-24hours  
 Duration time: 1.5hours/3hours  
 non-maintain type  
 IP20  
 Product size L: 415\*33\*31mm  
 Installation: Recessed mounted  
 Cut hole: 40mm  
 Diameter: 100mm  
 Box size: L300\*W70\*H65mm 1pc/box  
 Carton size: 48\*32\*35CM/30PCS/14.5KG

**Model: S920-140**  
 Input voltage: 220V ± 10% 50Hz  
 Input: 3W  
 Material: PC  
 LED SMD 3535 6V 3W  
 Battery: Lithium 3.7V 1800mAh  
 Charge time: 16-24hours  
 Duration time: 1.5hours/3hours  
 non-maintain type  
 IP20  
 Product size L: 415\*33\*31mm  
 Installation: Recessed mounted  
 Cut hole: 40mm  
 Diameter: 140mm  
 Box size: L300\*W70\*H65mm 1pc/box  
 Carton size: 48\*32\*35CM/30PCS/14.5KG

**Model: S919**  
 Input voltage: 220V ± 10% 50Hz  
 Output: 3W  
 Material: PC  
 LED SMD 2835  
 Battery: Ternary Lithium 3.7V 1800mAh (built-in)  
 Charge time: 16-24hours  
 Duration time: 1.5hours  
 non-maintain type  
 IP20  
 Product size: L: 95\*90mm  
 Recessed mounted  
 Cut hole: 82mm  
 Box size: 105\*105\*105mm, 1pc/box  
 Carton size: 54\*23\*55CM/50PCS/16.88KG



**Model: UFO-MINI**  
 Item size: 180\*25\*30mm  
 Cut hole: 42-50mm  
 Size for ceiling lamp: 55mm  
 Voltage: 85-265V 50/60Hz  
 Battery: Lithium 3.7V 2400mAh  
 Charging time: 24hours  
 Duration: 3hours  
 Material: plastic + aluminum



ALUMINUM



**Model: S801**  
 Item size: 110\*110\*30mm/200\*200\*30mm  
 Light source: 1pcs LED 1W  
 Voltage: AC85-265V, 50/60Hz  
 Battery: Ni-CD 1.2V 350mAh  
 Charging time: 24hours  
 Duration: 2hours  
 Material: aluminum  
 Operating mode: Emergency function



**Model: S205**  
 Item size: 270\*125\*52mm  
 Light source: 62pcs 2835 LED 6500k 3-8W  
 250-300lm  
 Voltage: AC86-265V, 50/60Hz  
 Battery: Lithium battery 3.7V 2400mAh  
 Charging time: 24hours  
 Duration: 3hours  
 Material: PS cover+ABS  
 IP Grade: IP20/IP65  
 installation: wall mounted/Recessed



**Model: S207**  
 Item size: 353\*119\*75mm  
 Voltage: AC85-265V, 50-60Hz  
 Light source: 30pcs SMD2835 LED 3W-8W/  
 1pcs 8W T5 tube/2pcs 8W T5, 50-60Hz  
 Battery: Lithium battery 3.7V 2400mAh  
 Charging Time: 24hours  
 Duration: 2hours  
 Material: PS cover+ABS  
 installation: wall mounted

IRON



**Model: S518**  
 Item size: 395\*193\*62mm  
 Light source: LED 12pcs LED 2835/3W  
 Voltage: AC220V, 50-60Hz  
 Battery: Lithium battery 3.7V 1500mAh  
 Charging time: 24hours  
 Duration: 2hours  
 Material: Iron



**Model: S516**  
 Item size: 350\*20\*150mm  
 Light source: LED 3W 4pcs/6pcs  
 Voltage: AC220V, 50-60Hz  
 Battery: Nickel-cadmium 1.2V 600mAh  
 Charging time: 24hours  
 Duration: 120mins  
 Material: Aluminum



PRODUCT CATALOG  
 EMERGENCY LIGHTING



ACRYLIC



**Model: S506**  
 Item size: 352\*28\*218mm  
 Voltage: AC86-265V, 50/60Hz  
 Light source: 6pcs SMD2835 LED 3W  
 Battery: Ni-CD battery 1.2V, 600mAh  
 Charging time: 24 hours  
 Duration: 120mins  
 Material: Plastic+acrylic

**Model: S509**  
 Item size: 360\*28\*200mm  
 Voltage: AC85-265V 50-60Hz  
 Light source: LED 8pcs/3W  
 Battery: Nickel-cadmium 1.2V 600mAh  
 Charging time: 24 hours  
 Duration: 120mins  
 Material: Acrylic, aluminum



**Model: S5501D**  
 Item size: 360\*28\*200mm  
 Voltage: AC85-265V 50-60Hz  
 Light source: LED 8pcs/3W  
 Battery: Nickel-cadmium 3.6V 300mAh  
 Charging time: 24hours  
 Duration: 120mins  
 Material: Aluminum, acrylic



**Model: S5501C**  
 Item size: 360\*28\*200mm  
 Voltage: AC85-265V 50-60Hz  
 Light source: LED 8pcs/3W  
 Battery: Nickel-cadmium 3.6V 300mAh  
 Charging time: 24hours  
 Duration: 120mins  
 Material: Aluminum, acrylic



**Model: S5503S**  
 Item size: 360\*28\*200mm  
 Voltage: AC85-265V 50-60Hz  
 Light source: LED 8pcs/3W  
 Battery: Nickel-cadmium 1.2V 600mAh  
 Charging time: 24hours  
 Duration: 120mins  
 Material: Aluminum, acrylic double sides

**EMERGENCY LIGHT  
TWO HEADS**



**Model:TM-S216**  
Item size:270\*65\*280mm  
Light source:LED 2\*2W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V 800mAh/1500mAh/  
Lead acid battery 6V 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:ABS plastic



**Model: S004**  
Item size: 310\*45\*240mm  
Light source: LED 3W  
Voltage: AC220, 50/60Hz  
Battery: nickel-cadmium 1.2V, 800mAh  
Charging time: 24 hours  
Emergency duration time: 1.5hours  
Material:Iron



**Model:S1018**  
Item size:270\*82\*295mm  
Light source:LED 2\*9W 2835SMD 2\*18PC  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V 800mAh  
Charging time:24hours  
Duration:2-10hours  
Material:Iron



**Model:E3W-OP**  
Item size:260\*50\*255mm  
Light source:LED3W  
Voltage:AC220V,50-60Hz  
Battery:NI-CD 1.2V 800mAh  
Charging time:24hours  
Duration:90mins  
Material:Iron



**Model:S1038**  
Item size:275\*70\*280mm  
Light source:LED 2\*0.5W/2\*2W/2\*5W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V600mAh/800mAh/1500mAh/Lead acid battery 6v 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:Iron



**Model:S1038**  
Item size:275\*70\*280mm  
Light source:LED 2\*0.5W/2\*2W/2\*5W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V600mAh/800mAh/1500mAh/Lead acid battery 6v 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:Iron



**Model:S003**  
Item size:265\*45\*250mm  
Light source:LED2\*0.5W/2\*2W  
Voltage:AC220V/110V,50-60Hz  
Battery:NI-CD1.2V 350mAh/3.6V 600mAh  
Charging time:24hours  
Duration:2hours  
Material:Iron



**Model:S003**  
Item size:265\*45\*250mm  
Light source:LED2\*0.5W/2\*2W  
Voltage:AC220V/110V,50-60Hz  
Battery:NI-CD1.2V 350mAh/3.6V 600mAh  
Charging time:24hours  
Duration:2hours  
Material:Iron



**Model:S001-T**  
Item size:275\*70\*280mm  
Light source:LED 2\*0.5W/2\*2W/2\*5W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V600mAh/800mAh/1500mAh/  
Lead acid battery 6v 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:Iron



**Model:S001**  
Item size:275\*70\*280mm  
Light source:LED 2\*0.5W/2\*2W/2\*5W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V600mAh/800mAh/1500mAh/  
Lead acid battery 6v 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:Iron



**Model: S508**  
Item size:340\*41.5\*255mm  
Light source: SMD2835\*20PCS  
Voltage: AC85-265V, 50/60Hz  
Battery: 3.2V1200mAh  
Charging time: 24 hours  
Emergency duration time: 2+hours  
Material:Acrylic,ABS+



**Model: S508**  
Item size:340\*41.5\*255mm  
Light source: SMD2835\*20PCS  
Voltage: AC85-265V, 50/60Hz  
Battery: 3.2V1200mAh  
Charging time: 24 hours  
Emergency duration time: 2+hours  
Material:Acrylic,ABS+



**Model:s1098**  
Item size:275\*70\*280mm  
Light source:LED2\*0.5W/2\*2W/  
2\*5W/2\*9W  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V600mAh/800mAh/  
1500mAh/Le ad acid battery 6v 4.5Ah  
Charging time:24hours  
Duration:2-10hours  
Material:ABS Plastic



**Model:s209**  
Size for emergency light:  
310\*140\*92mm  
Size for EXIT light:  
300\*46\*185mm  
Light source:LED SMD2835 2\*10PCS  
2\*2W/6pcs LED  
Voltage:AC85-265V,50-60Hz  
Battery:NI-CD3.6V 1000mAh  
Charging time:24hours  
Duration:2hours  
Material:ABS Plastic



**Model:S208**  
Item size:310\*140\*92mm  
Light source:LED MD28352\*10PCS2\*2W/2\*3W/2\*5W  
Voltage:AC85-265V 50-60Hz  
Battery:NI-CD3.6V800/1500mAh/NI-CD6V800/1500mAh  
charging time:24hours  
Duration:2-10hours  
Material:ABS



**Model:S218**  
Item size:280\*150\*45mm  
Light source:LED SMD 2835 3W  
Voltage:AC85-265V 50-60Hz  
Battery:NI-CD3.6V 800mAh  
charging time:24hours  
Duration:2hours  
Material:ABS Plastic



**Model:s1058**  
Item size:275\*140\*40mm  
Light source:COB6W  
Voltage:AC220V,50-60Hz  
Battery:NI-CD1.2V 600mAh  
Charging time:24hours  
Duration:90mins  
Material:Aluminum



**Model:S512-G**  
Item size:300\*46\*185mm  
Voltage:AC85-265V 50-60Hz  
Light source:F5 LED 6pcs  
Battery:Nickel-cadmium2.4V 300mAh  
charging time:24hours  
Duration:120mins  
Material:Plastic

GLASS



**Model:S504**  
Item size:345\*23\*140mm  
Voltage:AC220/110V 50-60Hz  
Light source: LED 3W 4pcs/6pcs  
Battery:Nickel-cadmium 1.2V 350mAh/600mAh  
Charging time: 24hours  
Duration:120mins  
Material:Aluminum, Glass



**Model:E2W-16**  
Item size:330\*23\*145mm  
Voltage:AC220V 50-60Hz  
Light source:LED 3W 4pcs  
Battery:Nickel-cadmium 1.2V 500mAh  
Charging time:24hours  
Duration:90mins  
Material:plastic,Iron



**Model:s507**  
Item size:330\*45\*247mm  
Light source:14pcs LED 2835 6000K  
Voltage:AC220V,50-60Hz  
Battery:NI-MH 1.2V,600mAh  
Charging time:24hours  
Duration:120mins  
Material:Plastic+LGP



REPLACEable UNIT SYSTEM  
CHANGE SIGNS anytime



**Model: ZR-B-BY001**

Item size:355\*65\*165mm  
Light source: LED 4W  
Voltage: AC220V, 50/60Hz  
Battery: NI-CD 1.2V,800mAh  
Charging time: 24hours  
Duration: 2hours  
Material: die casting aluminum+tempered glass



**Model: S510**

Item size:300\*180\*190mm  
Light source: LED  
Voltage: AC24-220V, 50Hz  
Battery: NI-CD 1.2V,300mAh  
Charging time: 24hours  
Duration: 1.5hours  
Material: aluminum



**Model: S520**

Item size:430\*160\*31mm  
Light source: LED 4W  
Voltage: AC220V, 50/60Hz  
Battery: NI-CD 1.2V,500mAh  
Charging time: 24hours  
Duration: 1.5hours  
Material: stainless steel+tempered glass



**Model: S513**

Item size:φ160\*38mm  
Light source: LED  
Voltage: AC24-220V, 50Hz  
Battery: NI-CD 1.2V,300mAh  
Charging time: 24hours  
Duration: 1.5hours  
Material: aluminum



**Model: S511**

Item size:φ160\*38mm  
Light source: LED  
Voltage: AC24-220V, 50Hz  
Battery: NI-CD 1.2V,500mAh  
Charging time: 24hours  
Duration: 1.5hours  
Material: aluminum



**Model: S005**

Item size:260\*50\*255mm  
Light source: LED 3W  
Voltage: AC220, 50/60Hz  
Battery: nickel-cadmium 1.2V,700mAh  
Charging time: 24hours  
Duration: 2hours  
Material: iron



**Model: S004**

Item size:310\*45\*240mm  
Light source: LED 3W  
Voltage: AC220, 50/60Hz  
Battery: nickel-cadmium 1.2V,800mAh  
Charging time: 24 hours  
Emergency duration time: 1.5hours  
material: iron  
2 years guarantee /maintain type  
CTN dimension:57.5\*31.5\*53.5cm /20pcs 11KG



**Model: S002**

Item size:265\*45\*250mm  
Light source: LED 2\*2W led5730 2\*4pcs  
Voltage: AC220V/110V, 50-60Hz  
Battery: NI-CD 3.6V 800mAh  
Charging time: 24hours  
Duration: 2hours  
Material: iron



**Model: S232**

Item size:310\*185\*70mm  
Color Temperature(CCT):6000K (Daylight Alert)  
Input Voltage(V):AC220-240V 50/60Hz  
Lamp Luminous Efficiency(lm/w):80  
Color Rendering Index(Ra):80  
Lifespan (hours):50000  
Working Time (hours):50000  
Bulb Type:LED  
Battery Type:Lead-Acid  
Material:ABS+plastic  
Usage:Fire protection  
Product Weight (kg) :1.55



**Model: S231**

Item size:310\*185\*70mm  
Color Temperature(CCT):6000K (Daylight Alert)  
Input Voltage(V):AC220-240V 50/60Hz  
Lamp Luminous Efficiency(lm/w):80  
Color Rendering Index(Ra):80  
Lifespan (hours):50000  
Working Time (hours):50000  
Bulb Type:LED  
Battery Type:Lead-Acid  
Material:ABS+plastic  
Usage:Fire protection  
Product Weight (kg) :1.55



**Model: S229**

Item size:260\*99\*170mm  
light source: SMD2835\*20PCS 10W  
voltage: AC85-265V, 50/60Hz  
Battery: Lithium 3.2V1200mAh  
Charging time: 24 hours  
Emergency duration time: 2+hours  
Material: ABS+PC/PS  
CTN dimension:  
Installation: wall mounted or ceiling mounted  
2 years guarantee /non-maintained type



**Model: S208**

Item size: 300\*140\*90mm  
Light source: 2\*10pcs LED2835  
Voltage: AC85-265V, 50/60Hz  
Battery: nickel-cadmium 3.6V,800mAh/  
1500mAh/ 1800mAh  
Charging time: 24hours  
Duration: 2hours  
Material: ABS material



**Model: S210**

Item size:280\*110\*68.5mm  
Light source: 2\*12pcs LED2835  
Voltage: AC85-265, 50/60Hz  
Battery: nickel-cadmium 3.6V,800mAh/1200mAh  
Charging time: 24hours  
Duration: 2hours  
Material: ABS material



**Model: S219**

Item size:300\*140\*90mm  
Light source: 2\*6pcs LED5730, 2\*2W  
Voltage: AC85-265, 50/60Hz  
Battery: Lithium 3.7V 2000mAh  
Charging time: 24hours  
Duration: 10hours  
Material: ABS material

**Model: S228**

Item size:260\*99\*48mm  
Light source: SMD2835\*20PCS 10W  
Voltage: AC85-265V, 50/60Hz  
Battery: Lithium 3.2V1200mAh  
Charging time: 24 hours  
Emergency duration time: 2+hours  
Material: ABS+PC/PS  
Installation: wall mounted or ceiling mounted  
2 years guarantee /non-maintained type



**Model: S228Frame**

Size:289\*128\*38mm  
Material: ABS+PC/PS



**Model: TM-S309**

Item size:φ220\*20mm  
Light source: LED  
Voltage: AC85-265V, 50/60Hz, 18W  
2 years guarantee  
CTN dimension: 46\*32.5\*25/20pcs /7.8KG



**Model: TM-S307-12W/18W**

Item size:φ230\*50mm/φ300\*50mm  
Light source: LED 2835, 12W /18W  
Voltage: AC180-265V, 50/60Hz  
Material: Plastic  
Function: Induction ceiling lamp



**Model: E3W-X**

Item size:D305\*105mm  
Light source: LED3W  
Voltage: AC220-240V, 50/60Hz  
Battery: NI-CD 1.2V,600mAh  
Emergency duration time: 90mins  
Material: Plastic  
2 years guarantee



**Model: TM-S313-8W/12W/15W**

tem size:95mm/120mm/145mm  
Cutting hole: 75mm/95mm/115mm  
Light source: LED 8W/12W/15W  
Voltage: AC220V, 50Hz  
Battery: Lithium 3.2V,500mAh  
Duration: 1.5hours



**Model: TM-S312-6W/8W/10W**

tem size:95mm/120mm/145mm  
Cutting hole: 75mm/95mm/115mm  
Light source: LED 6W/8W/10W, 6000K/3000K  
Battery: Lithium 3.2V,500mAh  
Voltage: AC220V, 50Hz  
Induction distance: 3-5m

INDUCTION



**Model: S302**

Item size:φ230\*50mm  
Light source: SMD5050 7W  
Input voltage:220-240V 50-60Hz  
Battery:NI-CD 2.4V 500mAh  
Duration:90mins  
Material:PC cover+ABS  
cct:6000k  
Emergency function or Sensor Or sound control

**Model: TM-S316-9W/15W/18W**

Item size:1200\*68\*34mm/900\*68\*34mm/1200\*68\*34mm  
Light source: LED 9W/15W/18W, 180pcs 2835  
Voltage: AC220V  
Induction distance: 5-8m  
Induction range: 120°  
Time lapse: 35S  
Luminance:5lux

